

3 YEARS WARRANTY



**IRIS-1**  
100mm Diameter



**IRIS-2**  
150mm X 200mm



**IRIS-3**  
87mm X 225mm

**IRIS LED** is a modern Foot range ideal for amenity lighting for both commercial or domestic applications. **IRIS LED** is available with 10w cool white 5000k LED that produces 910 lumens or a 10w warm white 2900k LED that produces 680 lumens. Available is a stainless steel cleaning kit that is essential to preserve the quality finish of the marine grade stainless steel

## FEATURES

- Aluminium Body Housing
- High product quality and robust design; long maintenance-free lifetime
- Compact, modern appearance ensures freedom of design for urban planners

## TECHNICAL SPECIFICATIONS

|                              |                          |
|------------------------------|--------------------------|
| On/Off Cycles:               | 35000                    |
| Correlated Color Temperature | 5800K                    |
| Color Rendering Index        | >80                      |
| PF                           | >0.9                     |
| THD                          | <20%                     |
| Finishing Color              | Polished Stainless Steel |
| Driver Integrated (Yes/No)   | Yes                      |

## ELECTRICAL SUPPLY

|                     |             |
|---------------------|-------------|
| Frequency (Hz)      | 50-60 Hz    |
| Mains voltage (VAC) | 220-240 VAC |

## APPLICATION CONDITIONS

|                             |               |
|-----------------------------|---------------|
| Operating Temperature range | -20 to +50 °C |
| Nominal Temperature         | 25 °C         |

## MATERIAL PROPERTIES

|                  |                        |
|------------------|------------------------|
| Optical Material | Polycarbonate diffuser |
| Housing          | Aluminium              |

Gardens, parking areas

Building Exteriors

Commercial plazas

Residential areas

| ORDER CODE  | PART NO         | POWER (WATT) |
|-------------|-----------------|--------------|
| 36-ZWW1C2-5 | IRIS-1-ZWW1C2-5 | 5            |
| 36-ZWW1E2-5 | IRIS-2-ZWW1E2-5 | 5            |
| 36-ZWW1C2-5 | IRIS-3-ZWW1C2-5 | 5            |