



**ATLAS** LED is a modern bollard range ideal for amenity lighting for both commercial or domestic applications. **ATLAS** LED is available with 10W/20W/30W cool white 5000k LED that produces 910 lumens or a 10W/20W warm white 2900k LED that produces 680 lumens. Also available is a stainless steel cleaning kit that is essential to preserve the quality finish of the marine grade stainless steel or MS

## FEATURES

- Automatic On-Off control system - Optional
- High product quality and robust design; long maintenance-free lifetime
- Compact, modern appearance ensures freedom of design for urban planners



## TECHNICAL SPECIFICATIONS

On/Off Cycles:	35000
Correlated Color Temperature	2900K
Color Rendering Index	>80
PF	>0.9
Finishing Color	Powder Coated
Driver Integrated (Yes/No)	Yes

## ELECTRICAL SUPPLY

Frequency (Hz)	50-60 Hz
Mains voltage (VAC)	220-240 VAC

## APPLICATION CONDITIONS

Operating Temperature range	-20 to +50 °C
Nominal Temperature	25 °C

## MATERIAL PROPERTIES

Optical Material	Acrylic diffuser Milky white/Transparent
Housing	MS with Powder Coated

Gardens, parking areas

Building Exteriors

Commercial plazas

Residential areas

PART NO	POWER (WATT)	HEIGHT
ATLAS-Z1-10	10	1FT
ATLAS-Z2-10	10	3FT
ATLAS-Z3-20	20	4FT
ATLAS-Z4-30	30	6FT